

IPSEC Guard Tour System (GTS) - Features Comparison Chart

MODEL	P-ES	P5	P4-S	P8	P1	L-4D	PZ	P-4D	PZ-G
	OFFLINE					ONLINE			
Device Photo									
Communication	Magnetic USB	Magnetic USB	Magnetic USB	Magnetic USB or docking station	Magnetic USB	4G Magnetic USB	4G Magnetic USB	4G Magnetic USB	4G Magnetic USB
Reading Type	Touch Button	RFID 125Khz	RFID 125Khz	RFID 125Khz & 2.4G	RFID 125Khz	RFID 125Khz	RFID 125Khz	RFID 125Khz	RFID 125Khz
Flashlight	√	x	√	√	√	x	x	x	x
Screen	x	x	x	√	√	√	√	√	√
Screen Type	x	x	x	OLED 128 * 64	OLED 128 * 64	OLED 128 * 64	OLED 128 * 64	OLED 128 * 64	OLED 128 * 64
Low Battery Warning	√	√	√	√	√	√	√	√	√
Rechargeable Lithium Battery	700mAh	880mAh	1150mAh	1150mAh	2000mAh	3400mAh	3400mAh	3400mAh	3400mAh
Fingerprint identification	x	x	x	x	√	x	√	x	√
Impact Records	√	x	x	x	√	√	√	√	√
Alarm sending	x	x	x	x	x	√	√	√	√
Alarm button	x	x	x	x	x	√	√	√	√
Degree of protection	IP67								
Shockproof housing	√	√	√	√	√	√	√	√	√
Working temperature	-40 to + 85C								
Online monitoring	x	x	x	x	x	√	√	√	√
GPS monitoring	x	x	x	x	x	x	x	√	√
Voice assistant	x	x	x	x	√	√	√	√	√
LED notification	Multi-color	Multi-color	Multi-color	Multi-color	x	Multi-color	Multi-color	Multi-color	Multi-color
Event Recording (memory)	√	√	√	√	√	√	√	√	√
Event sending function	√	√	√	√	√	√	√	√	√
Pedometer (pedometer)	√	x	x	x	√	x	x	x	x
Mandown / Drop sensor	√	x	x	x	√	x	x	x	x

